



Model		CTD12R-E
Load capacity	Kg	1200
Load centre distance	c(mm)	600
Load distance, center of drive axle to fork	x(mm)	770
Fork height, lowered	h13(mm)	80
Tyre size, front	mm	195x70
Tyre size, rear	mm	98x82
Addition wheels (dimensions)	mm	150x60
wheels, number front and rear		4
Height, mast lowered	h1(mm)	2145
Max lift height	h3(mm)	3300
Height with mast extended	h4(mm)	3600
Height of tiller in drive position min/max.	h14(mm)	670/1300
Overall length	l1(mm)	1500
length to face of forks	l2(mm)	660
Overall width	b1(mm)	1132-1532
Fork dimensions	s/e/l(mm)	35/100/1150
Width overall forks	b5(mm)	200-800
Ground clearance, centre of wheel base	m2(mm)	35
Aisle width for pallets 1000x1200 crossways	Ast(mm)	2280
Aisle width for pallets 800x1200 crossways	Ast(mm)	2280
Turning radius	Wa(mm)	1490
Travel speed, laden/unladen	Km/h	4.5/5
Lift speed, laden/unladen	m/s	0.09/0.14
Lowering speed, laden/unladen	m/s	0.12/0.10
Battery voltage, nominal capacity	V/Ah	24/105
Battery weight	Kg	60
Battery dimensions l/w/h	mm	260x171x217
Service weight(without battery)	Kg	660

Charging time	hrs	8
Working time	hrs	8